SAFETY DATA SHEET



1. Identification

Product identifier BEADEX® Topping Joint Compound, Ready-Mixed

Other means of identification

SDS number 61000010025

Synonyms Joint Compound (Ready-Mixed), Taping Compound, Mud, Finishing Compound

Recommended use Interior use.

Recommended restrictionsUse in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name United States Gypsum Company

Address 550 West Adams Street

Chicago, Illinois 60661-3637

Telephone 1-800-874-4968
Website www.usg.com
Emergency phone number 1-800-507-8899

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.

Signal word None.

Hazard statement None.

Precautionary statement

PreventionObserve good industrial hygiene practices.ResponseGet medical attention/advice if you feel unwell.

Storage Store as indicated in Section 7.

Disposal Dispose of in accordance with local, state, and federal regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	
Calcium carbonate	1317-65-3	> 60

Composition comments All concentrations are in percent by weight unless ingredient is a gas.

Industrial hygiene studies by USG Corporation and governmental agencies did not detect airborne respirable crystalline silica above OSHA permissible exposure limits (PELs) during activities associated with the normal use of this product, though in some cases total dust PELs were exceeded. However, job site air monitoring should be conducted to determine actual exposure when PELs may be exceeded.

4. First-aid measures

Inhalation Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move

injured person into fresh air and keep person calm under observation. Get medical attention if

symptoms persist.

Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or Skin contact

persists.

Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical Eye contact

assistance.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system causing sneezing and/or coughing. May cause allergic skin disorders in sensitive individuals.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Use fire-extinguishing media appropriate for surrounding materials.

Not applicable.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Not a fire hazard.

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

Specific methods

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Cool material exposed to heat with water spray and remove it if no risk is involved.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up

Large Spills: Scoop spilled materials and recover as much of the product as possible for use. If spillage is unrecoverable dispose according to local, state, and federal regulations.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling

Avoid inhalation of dust and contact with skin and eyes. Minimize dust generation and accumulation. In case of insufficient ventilation, wear suitable respiratory equipment. Observe good industrial hygiene practices. Use proper lifting techniques.

Conditions for safe storage, including any incompatibilities Store in a cool, dry, well-ventilated place. Store in a closed container away from incompatible materials. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Keep containers closed when not in use.

Filled 4.5 gallon pails of joint compound may be stacked a maximum of 3 layers high on a standard 48 x 48 pallet (16 pails per layer, 3 layers high). Pallets may only be stacked a maximum of two high.

Filled cartons of joint compound may be stacked a maximum of 3 layers high on a standard 42 x 42 or 42 x 48 pallet (16 pails per layer, 3 layers high). Pallets may only be stacked a maximum of two high.

8. Exposure controls/personal protection

Occupational exposure limits

918359

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Version #: 02 Revision date: 30-March-2016 Issue date: 21-January-2014

Components	Type	Value	Form
Calcium carbonate (CAS 1317-65-3)		5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. NIOSH: Pocket Guide to Chemical Hazards

ComponentsTypeValueFormCalcium carbonate (CAS 1317-65-3)TWA5 mg/m3Respirable.10 mg/m3Total

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering Provide sufficient ventilation for operations causing dust formation. Observe occupational

controls exposure limits and minimize the risk of exposure.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved safety goggles.

Skin protection

Hand protection It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin

contact use suitable protective gloves.

Skin protection

Other Normal work clothing (long sleeved shirts and long pants) is recommended.

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator

use.

Thermal hazards None.

General hygiene Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment separately from regular wash. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Physical stateSemi-solid.FormPaste.ColorOff-white.

Odor Low to no odor.
Odor threshold Not applicable.

pH 7.5 - 9.9

Melting point/freezing point Not applicable.

Initial boiling point and boiling 212 °F (100 °C)

range

Flash point Not applicable.

Evaporation rate Not applicable.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower Not applicable.

(%)

Not applicable.

Flammability limit - upper

(%)

Explosive limit - lower (%) Not applicable.

Explosive limit - upper (%) Not applicable.

Not applicable.

Vapor pressureNot applicable.Vapor densityNot applicable.Relative density1.4 - 1.8 (H2O=1)

Solubility(ies)

Solubility (water) Soluble in water.

Partition coefficient (n-octanol/water)

Not applicable.

Auto-ignition temperature

Decomposition temperature

Viscosity

Not applicable.

Not applicable.

Other information

Bulk density 12 - 15 lb/gal

VOC (Weight %) 0.1 g/l (Calculated by EPA Method 24)

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stabilityMaterial is stable under normal conditions.Possibility of hazardousHazardous polymerization does not occur.

reactions

Conditions to avoid None known.

Incompatible materials None known.

Hazardous decomposition None known.

Above 1472°F (800°C) limestone (CaCO3) can decompose to lime (CaO) and release carbon

products dioxide (CO2).

11. Toxicological information

Information on likely routes of exposure

Inhalation Airborne dust may irritate throat and upper respiratory system causing coughing.

Skin contact May cause allergic skin reactions especially in individuals with pre-existing skin disease such as

eczema. (See Section 16).

Eye contact Airborne dust may cause mechanical eye irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system

causing sneezing and/or coughing.

Information on toxicological effects

Acute toxicity

Not expected to be a hazard under normal conditions of intended use.

Skin corrosion/irritation

Prolonged or repeated skin contact may cause drying, cracking, or irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization The product contains a small amount of sensitizing substance which may provoke an allergic

reaction among sensitive individuals after repeated contact.

For detailed information, see section 16.

Germ cell mutagenicity Data does not suggest that this product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not expected to increase the risk of cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity Not expected to be a reproductive hazard.

Specific target organ toxicity - single exposure

No data available, but none expected.

Specific target organ toxicity -

repeated exposure

Not classified.

repeated expessive

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged exposure may cause chronic effects. For detailed information, see section 16.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data available.

Bioaccumulative potential Bioaccumulation is not expected.

Mobility in soilNo data available.Other adverse effectsNone expected.

13. Disposal considerations

Disposal instructionsDispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.

Local disposal regulations Dispose of in accordance with local regulations.

Hazardous waste code Not regulated.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulationsThis product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

All components of this product are in compliance with the listing Requirements of the U.S. Toxic

Substances Control Act (TSCA) Chemical Substance Inventory.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

BEADEX® Topping Joint Compound, Ready-Mixed

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Calcium carbonate (CAS 1317-65-3)

US. New Jersey Worker and Community Right-to-Know Act

Calcium carbonate (CAS 1317-65-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Calcium carbonate (CAS 1317-65-3)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Attapulgite (CAS 12174-11-7)

16. Other information, including date of preparation or last revision

Issue date21-January-2014Revision date30-March-2016

Version # 02

Further information Attapulgite: Carcinogenic to experimental animals via a route of exposure not relevant to human

exposure per ACGIH.

Skin Sensitization Potential: This product contains an amount of Triazinetriethanol (THT) (CAS No.

4719-04-4) that is within the approved EPA regulated limits. THT can act as a sensitizer.

Numerous human studies with concentrations up to 1% yielded negative (no sensitization) results. However, some results showed positive reactions in concentrations <0.5% mostly in persons with

eczema.

Crystalline silica: Raw materials in this product may contain respirable crystalline silica as an impurity. Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

Bucket NFPA Classification:

Health: 0 Flammability: 1 Physical hazard: 0

NFPA Ratings: Health: 1 Flammability: 0 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings



List of abbreviations NFPA: National Fire Protection Association.

References Registry of Toxic Effects of Chemical Substances (RTECS)

HSDB® - Hazardous Substances Data Bank

Torben et al. (2001). Environmental and Health Assessment of Substances in Household

Detergents and Cosmetic Products.

Disclaimer This information is provided without warranty. The information is believed to be correct. This

information should be used to make an independent determination of the methods to safeguard

workers and the environment.