

SAFETY DATA SHEET

Creation Date 26-Oct-2009	Revision Date 17-Jan-2018	Revision Number 4
	1. Identification	
Product Name	Hexane	
Cat No. :	BP2615-100; H307-4; H334-1; H334-4; N3-2	0; N3-200; N3S-4; O3386-20
CAS-No Synonyms	110-54-3 n-Hexane with < 5% various methyl pentanes; Ligroine; (Anhydrous/Certified ACS/Pesticide/HPLC/OPTIMA/GC Resolv/Spectranalyzed/Technical/Laboratory)	•
Recommended Use Uses advised against	Laboratory chemicals. Not for food, drug, pesticide or biocidal product use	
Details of the supplier of the sa	ifety data sheet	
Company Fisher Scientific One Reagent Lane		

One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

Emergency Telephone Number

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

Г

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Skin Corrosion/irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system, Central nervous system	stem (CNS).
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Liver, Heart, Blood.	
Aspiration Toxicity	Category 1

Label Elements

Signal Word Danger

Hazard Statements

Highly flammable liquid and vapor May be fatal if swallowed and enters airways Causes skin irritation Causes serious eye irritation May cause respiratory irritation May cause drowsiness or dizziness Suspected of damaging fertility Causes damage to organs through prolonged or repeated exposure



Precautionary Statements Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge Keep cool

Response

IF exposed or concerned: Get medical attention/advice

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Toxic to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component		CAS-No	Weight %
Hexane		110-54-3	>95
	4.	First-aid measures	
Eye Contact	Rinse immed medical atten	iately with plenty of water, also under th tion.	ne eyelids, for at least 15 minutes. Get
Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Obtain media		t 15 minutes. Obtain medical attention.	
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth meth victim ingested or inhaled the substance; give artificial respiration with the aid of a poch mask equipped with a one-way valve or other proper respiratory medical device. Obtain medical attention. Aspiration into lungs can produce severe lung damage.		al respiration with the aid of a pocket respiratory medical device. Obtain
Ingestion	Do not induce vomiting. Call a physician or Poison Control Center immediately. If vom occurs, lean victim forward to reduce the risk of aspiration.		
Most important symptoms and effects Notes to Physician	Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting Treat symptomatically		
	5. Fi	re-fighting measures	
Suitable Extinguishing Media	CO 2, dry che with water sp		Cool closed containers exposed to fire
Unsuitable Extinguishing Media		e ineffective, This material is lighter that be spread by the use of water in an area	
Flash Point	-22 °C / -7.	6 °F	
Method -	No information available		
Autoignition Temperature	223 °C / 43	33.4 °F	
Explosion Limits Upper Lower Sensitivity to Mechanical Impac Sensitivity to Static Discharge	7.5 vol % 1.1 vol % t No informatio No informatio		

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO₂)

Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

<u>NFPA</u> Health 2	Flammability 3	Instability 0	Physical hazards N/A
	6. Accidental re	lease measures	
Personal Precautions			ntilation. Evacuate personnel to onary measures against static

Environmental Precautions	Do not flush into surface water or sanitary sewer system. Avoid release to the environment. Collect spillage.
Methods for Containment and Clean Up	Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges.
	7. Handling and storage
Handling	Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Do not breathe vapors or spray mist. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use explosion-proof equipment. Take precautionary

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Flammables area.

measures against static discharges. To avoid ignition of vapors by static electricity

8. Exposure controls / personal protection

discharge, all metal parts of the equipment must be grounded.

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Hexane	TWA: 50 ppm Skin	(Vacated) TWA: 50 ppm (Vacated) TWA: 180 mg/m ³	IDLH: 1100 ppm TWA: 50 ppm	TWA: 50 ppm TWA: 176 mg/m ³
		TWA: 500 ppm TWA: 1800 mg/m ³	TWA: 180 mg/m ³	Ĵ

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures	Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment.
Personal Protective Equipment	
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

	9. Physical and chemical properties
Physical State	Liquid
Appearance	Colorless
Odor	Petroleum distillates
Odor Threshold	No information available
рН	Not applicable
Melting Point/Range	-95 °C / -139 °F
Boiling Point/Range	69 °C / 156.2 °F @ 760 mmHg

Flash Point
Evaporation Rate
Flammability (solid,gas)
Flammability or explosive limits
Upper
Lower
Vapor Pressure
Vapor Density
Specific Gravity
Solubility
Partition coefficient; n-octanol/water
Autoignition Temperature
Decomposition Temperature
Viscosity
Molecular Formula
Molecular Weight

-22 °C / -7.6 °F No information available Not applicable

7.5 vol % 1.1 vol % 160 mbar @ 20 °C 2.97 0.659 immiscible No data available 223 °C / 433.4 °F No information available 0.31 mPa s at 20 °C C6 H14 86.18

10. Stability and reactivity		
Reactive Hazard	None known, based on information available	
Stability	Stable under normal conditions.	
Conditions to Avoid	Incompatible products. Heat, flames and sparks. Exposure to light. Keep away from open flames, hot surfaces and sources of ignition.	
Incompatible Materials	Strong oxidizing agents, Halogens	
Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)		
Hazardous Polymerization	Hazardous polymerization does not occur.	
Hazardous Reactions	None under normal processing.	

11. Toxicological information

Acute Toxicity

Product Information Component Informati

Component		LD50 Oral		LD50 Dermal	LC50	Inhalation	
Hexane		LD50 = 25 g/kg (Rat)	LD50 = 3	3000 mg/kg (Rabbit)	LC50 = 4800	0 ppm (Rat)4 h	
Foxicologically Syr Products Delayed and immed	-		No information available vell as chronic effects from short and long-term exposure				
rritation		Irritating to eyes and	l skin				
Sensitization		No information available					
Sensitization		No information availa	able				
Sensitization Carcinogenicity				ach agency has listed	any ingredient	as a carcinoger	
	CAS-No			ach agency has listed	any ingredient a	as a carcinoger Mexico	
Carcinogenicity	CAS-No 110-54-3	The table below indi	cates whether ea		, ,	<u> </u>	
Carcinogenicity Component		The table below indi IARC Not listed	cates whether ea NTP Not listed	ACGIH	OSHA	Mexico	
Carcinogenicity Component Hexane	110-54-3	The table below indi IARC Not listed Mutagenic effects ha	cates whether ea NTP Not listed ave occurred in e	ACGIH Not listed	OSHA Not listed	Mexico Not listed	

Teratogenicity	Teratogenic effects have occurred in experimental animals.
STOT - single exposure STOT - repeated exposure	Respiratory system Central nervous system (CNS) Liver Heart Blood
Aspiration hazard	No information available
Symptoms / effects,both acute and delayed	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Endocrine Disruptor Information	No information available
Other Adverse Effects	Tumorigenic effects have been reported in experimental animals. See actual entry in RTECS for complete information.

12. Ecological information

Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea	
Hexane	Not listed	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	Not listed	EC50: 3.87 mg/L/48h	
Persistence and Degradability Persistence is unlikely based on information available					

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility

Will likely be mobile in the environment due to its volatility.

Component	log Pow
Hexane	4.11

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT	
UN-No	UN1208
Proper Shipping Name	Hexanes
Hazard Class	3
Packing Group	II
TDG	
UN-No	UN1208
Proper Shipping Name	HEXANES
Hazard Class	3
Packing Group	II
IATA	
UN-No	UN1208
Proper Shipping Name	Hexanes
Hazard Class	3
Packing Group	II
IMDG/IMO	
UN-No	UN1208
Proper Shipping Name	Hexanes
Hazard Class	3

Packing Group Ш 15. Regulatory information

All of the components in the product are on the following Inventory lists: Australia Complete Regulatory Information contained in following SDS's X = listed China Canada The product is classified and labeled according to EC directives or corresponding national laws The product is classified and labeled in accordance with Directive 1999/45/EC Europe TSCA Korea Philippines Japan U.S.A. (TSCA) Canada (DSL/NDSL) Europe (EINECS/ELINCS/NLP) Australia (AICS) Korea (ECL) China (IECSC) Japan (ENCS) Philippines (PICCS)

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Hexane	Х	Х	-	203-777-6	438-390		Х	Х	Х	Х	Х
					-3						

Legend: X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Not applicable

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Hexane	110-54-3	>95	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Hexane	Х		-

OSHA Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component		Hazardous Substances RQs	CERCLA EHS RQs	
Hexane		5000 lb	-	
California Proposition 65	This product does not contain any Proposition 65 chemicals			

California Proposition 65

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island

Hexane X X X X X X						
	Hexane	Х	Х	Х	Х	Х

U.S. Department of Transportation

Reportable Quantity (RQ):	Υ
DOT Marine Pollutant	Ν
DOT Severe Marine Pollutant	Ν

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Serious risk, Grade 3

	16. Other information
Prepared By	Regulatory Affairs
	Thermo Fisher Scientific
	Email: EMSDS.RA@thermofisher.com
Creation Date	26-Oct-2009
Revision Date	17-Jan-2018
Print Date	17-Jan-2018
Revision Summary	This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS