

ACE		HEALTH	1
Hardware	MATERIAL SAFETY DATA SHEET	FLAMMABILITY	1
		REACTIVITY	0
		PERSONAL PROTECTION	B

FOR COATINGS. RESINS AND RELATED MATERIALS
 (Approved by U S Department of Labor "ESSENTIALLY SIMILAR to Form OSHA 174)

Product: 182A100, 101, 128, 180, 181, 182, 186, 188, 200, 210, 211, 214, 215
 ROYAL TOUCH SATIN LATEX ACRYLIC WALL ANDTRIM PAINT

SECTION I

Manufacture's Name	Emergency Telephone Number
Paint Division, Ace Hardware Corporation	(708) 990-6600
ADDRESS (Number' Street CITY State and Zip Code)	Telephone Number for Information
21901 S. Central Ave.	(708) 720-0600
Matteson IL 60443	Date Prepared
	JULY 1, 1997
	Signature of Preparer (optional)

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components (Specific Chemical identity Common Name(s))	OSHA PEL	ACGIH TLV	% (optional)
Titanium Dioxide CAS# 13463-67-7	10 Mg/M3	10 Mg/M3	23.5
Calcium Carbonate CAS# 1317-65-3	15(5) Mg/M3	10 Mg/M3	9.9
Nepheline Syenite CAS# 37244-96-5	5Mg/M3	10 Mg/M3	20.0
Magnesium Aluminum Silicate CAS# 12174-11-7	15 Mg/M3	10 Mg/M3	0.1
Aliphatic Petroleum Distillate CAS# 64741-88-4			0.8
Aluminum Silicate CAS# 66402-68-4	5 Mg/M3	5 Mg/M3	6.0
Ester Alcohol CAS# 25265-77-4	Not Est.	Not Est.	1.6
Propylene Glycol CAS# 57-55-6	None	None	4.9
Ammonium Hydroxide CAS# 1336-21-6	50 PPM	25 PPM	< 0.1
Nonylphenoxypolyethanol CAS# 68412-54-4	Not Est.	Not Est.	0.5
2-Amino-2-Methyl 1- Propanol CAS# 124-68-5	20 PPM	10 PPM	0.1

SECTION III- PHYSICAL/CHEMICAL CHARACTERISTIC

Boiling Point 212 °F	Specific Gravity (H2O = 1) 1.32
Vapor Pressure (mm HG.) N/A	Melting Point N/A
Vapor Density (AIR = 1) Heavier Than Air	Evaporation Rate (Butyl Acetate = 1) Slower Than Ether
Soluble in Water Dilutable	
Appearance and Odor White Pigmented liquid with slight odor.	

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used) 199 °F PMCC	Flammable Limits	LEL N/A	UEL N/A	N/A	N/A
Extinguishing Media Non-combustible - for dry solids use water, foam CO2, dry chemicals					
Special Fire Fighting Procedures Full Protective equipment including self-contained breathing apparatus					

Preferable

Mechanical (General)
Acceptable

Other

Protective Gloves
For use with in
Sect. II materials

Eye Protection
Safety spectacles w/unperforated
side shield

Other Protective Clothing or Equipment

Work/Hygienic Practices

Avoid breathing vapor or spray mist. Avoid contact with skin or eyes.