



SAFETY DATA SHEET

1. Identification

Product identifier **BEADEX® Lite Topping Joint Compound, Ready-Mixed**

Other means of identification

SDS number 61000010022

Synonyms Joint Compound (Ready-Mixed) , Taping Compound, Mud, Finishing Compound

Recommended use Interior use.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer / Importer / Supplier / Distributor information

Company name United States Gypsum Company
Address 550 West Adams Street
 Chicago, Illinois 60661-3637

Telephone 1-800-874-4968
Website www.usg.com
Emergency phone number 1-800-507-8899

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.
Hazard statement None.

Precautionary statement

Prevention Observe good industrial hygiene practices.
Response Get medical attention/advice if you feel unwell.
Storage Store as indicated in Section 7.
Disposal Dispose of in accordance with local, state, and federal regulations.

Hazard(s) not otherwise classified (HNOC) Not classified.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Limestone	1317-65-3	< 40
Perlite	93763-70-3	< 10
Attapulgit	12174-11-7	< 5

Composition comments All concentrations are in percent by weight unless ingredient is a gas.

Industrial hygiene studies by USG Corporation and governmental agencies did not detect airborne respirable crystalline silica above OSHA permissible exposure limits (PELs) during activities associated with the normal use of this product, though in some cases total dust PELs were exceeded. However, job site air monitoring should be conducted to determine actual exposure when PELs may be exceeded.

4. First-aid measures

Inhalation Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist.

Skin contact Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or persists.

Eye contact Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system causing sneezing and/or coughing. May cause allergic skin disorders in sensitive individuals.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	Not applicable.
Specific hazards arising from the chemical	Not a fire hazard.
Special protective equipment and precautions for firefighters	Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Use standard firefighting procedures and consider the hazards of other involved materials.
Specific methods	Cool material exposed to heat with water spray and remove it if no risk is involved.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	See Section 8 of the SDS for Personal Protective Equipment.
Methods and materials for containment and cleaning up	Large Spills: Scoop spilled materials and recover as much of the product as possible for use. If spillage is unrecoverable dispose according to local, state, and federal regulations. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling	Avoid inhalation of dust and contact with skin and eyes. Minimize dust generation and accumulation. In case of insufficient ventilation, wear suitable respiratory equipment. Observe good industrial hygiene practices. Use proper lifting techniques.
Conditions for safe storage, including any incompatibilities	Store in a cool, dry, well-ventilated place. Store in a closed container away from incompatible materials. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Keep containers closed when not in use. Filled 4.5 gallon pails of joint compound may be stacked a maximum of 3 layers high on a standard 48 x 48 pallet (16 pails per layer, 3 layers high). Pallets may only be stacked a maximum of two high. Filled cartons of joint compound may be stacked a maximum of 3 layers high on a standard 42 x 42 or 42 x 48 pallet (16 pails per layer, 3 layers high). Pallets may only be stacked a maximum of two high.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Limestone (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US NIOSH Pocket Guide to Chemical Hazards: Recommended exposure limit (REL)

Components	Type	Value	Form
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Perlite (CAS 93763-70-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total

Biological limit values	No biological exposure limits noted for the ingredient(s).
--------------------------------	--

Appropriate engineering controls	Provide sufficient ventilation for operations causing dust formation. Observe occupational exposure limits and minimize the risk of exposure.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear approved safety goggles.
Skin protection	
Hand protection	It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin contact use suitable protective gloves.
Other	Normal work clothing (long sleeved shirts and long pants) is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use.
Thermal hazards	None.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Physical state	Semi-solid.
Form	Paste.
Color	Off-white.
Odor	Low to no odor.
Odor threshold	Not applicable.
pH	7.5 - 9.9
Melting point/freezing point	Not applicable.
Initial boiling point and boiling range	212 °F (100 °C)
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.
Vapor pressure	Not applicable.
Vapor density	Not applicable.
Relative density	1 - 1.3 (H ₂ O=1)
Solubility(ies)	Soluble in water.
Partition coefficient (n-octanol/water)	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not applicable.
Viscosity	Not applicable.
Other information	
Bulk density	8.3 - 11 lb/gal
VOC (Weight %)	11.8 g/l (Calculated by EPA Method 24)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	None known.
Incompatible materials	None known.
Hazardous decomposition products	Above 1472°F (800°C) limestone (CaCO ₃) can decompose to lime (CaO) and release carbon dioxide (CO ₂).

11. Toxicological information

Information on likely routes of exposure

Ingestion	May cause discomfort if swallowed.
Inhalation	Airborne dust may irritate throat and upper respiratory system causing coughing.
Skin contact	May cause allergic skin reactions especially in individuals with pre-existing skin disease such as eczema. (See Section 16).
Eye contact	Airborne dust may cause mechanical eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system causing sneezing and/or coughing.

Information on toxicological effects

Acute toxicity	Not expected to be a hazard under normal conditions of intended use.
Skin corrosion/irritation	Prolonged or repeated skin contact may cause drying, cracking, or irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	The product contains a small amount of sensitizing substance which may provoke an allergic reaction among sensitive individuals after repeated contact. For detailed information, see section 16.
Germ cell mutagenicity	Data does not suggest that this product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not expected to increase the risk of cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Attapulgit (CAS 12174-11-7)	2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans.
-----------------------------	--

Reproductive toxicity	Not expected to be a reproductive hazard.
Specific target organ toxicity - single exposure	No data available, but none expected.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged exposure may cause chronic effects. For detailed information, see section 16.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data available.
Bioaccumulative potential	Bioaccumulation is not expected.
Mobility in soil	No data available.
Other adverse effects	None expected.

13. Disposal considerations

Disposal instructions	Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.
Local disposal regulations	Dispose of in accordance with local regulations.
Hazardous waste code	Not regulated.
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Dispose of in accordance with local regulations.

14. Transport information

DOT

Not regulated as a hazardous material by DOT.

IATA

Not regulated as a dangerous good.

IMDG

Not regulated as a dangerous good.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Limestone (CAS 1317-65-3)

Perlite (CAS 93763-70-3)

US. New Jersey Worker and Community Right-to-Know Act

Limestone (CAS 1317-65-3)

Perlite (CAS 93763-70-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Limestone (CAS 1317-65-3)

Perlite (CAS 93763-70-3)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Attapulgite (CAS 12174-11-7)

International Inventories

All components of this product are in compliance with the listing Requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. Other information, including date of preparation or last revision

Issue date 21-January-2014

Revision date 25-March-2016

Version # 02

Further information

Attapulgit: Carcinogenic to experimental animals via a route of exposure not relevant to human exposure per ACGIH.

Skin Sensitization Potential: This product contains an amount of Triazinetriethanol (THT) (CAS No. 4719-04-4) that is within the approved EPA regulated limits. THT can act as a sensitizer. Numerous human studies with concentrations up to 1% yielded negative (no sensitization) results. However, some results showed positive reactions in concentrations <0.5% mostly in persons with eczema.

Crystalline silica: Raw materials in this product may contain respirable crystalline silica as an impurity. Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

Bucket NFPA Classification:

Health: 0

Flammability: 1

Physical hazard: 0

NFPA Ratings:


Health: 1

Flammability: 0

Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA Ratings



List of abbreviations

NFPA: National Fire Protection Association.

References

Registry of Toxic Effects of Chemical Substances (RTECS)

HSDB® - Hazardous Substances Data Bank

Torben et al. (2001). Environmental and Health Assessment of Substances in Household Detergents and Cosmetic Products.

Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.